

# MOTOR OIL TREATMENT + PTFE (TEFLON<sup>®</sup>)

Product ID: 80034

## **Product description**

PTFE (Teflon) based oil additive significantly reducing friction, wear and engine noise. Reduces fuel and oil consumption and restores engine power.

#### **Benefits**

- ✓ Reduces friction and wear due to formation of a Teflon lubricating film inside the engine
- ✓ Reduces fuel consumption
- ✓ Restores engine power and optimizes performance
- ✓ Reduces emission of hazardous exhaust gases
- ✓ Provides emergency lubrication
- ✓ Reduces engine noise level
- ✓ Increases engine lifetime

## Usage

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters.

## Direction

Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Make sure the oil contents do not exceed the maximum oil level in your engine.

## Dosage

One bottle treats 3 to 6 litres of motor oil.

## **Technical specification**

Density g/cm³: 0,891 Colour: Cream

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**