



DRY-FILM LUBRICANT + PTFE

Product ID: 80508

Product description

Dry-Film Lubricant + PTFE is a high-grade, grease-free lubricant for long-term protection with a deeply penetrating power. It is a strong adhesive that makes for very smooth action between components, even under extreme conditions. It possesses excellent water and moisture-repellent properties. Dry-film lubricant + PTFE is a perfectly suitable product for all purposes where components are to be lubricated, but not with a greasy lubricant.

Benefits

- ✓ Reduces friction and prolongs service life of the components
- ✓ Affords corrosion protection
- ✓ Temperature range between - 50°C and + 260°C
- ✓ Water and moisture-repellent
- ✓ Resistant to cold, warm and salt water
- ✓ Stops annoying squeaks

Usage

Anti-seize and lubricating agent for chains, nylon bearings, sliding surfaces, cables, etc. Ideal for automotive window runners and sunroof guides.

Direction

Shake well before use. Substrates should be clean and dry. Spraying distance approximately 20 cm.

Dosage

To be used whenever required.

The information in this sheet is correct and true to the best of our knowledge, but any recommendations or suggestions made in this sheet are made without guarantee since the conditions of use are beyond our control. We do not accept responsibility for damage as a consequence of incompleteness, negligence and/or inaccuracies in this information sheet. The above typical values do not constitute a specification nor does the information in this sheet imply any legally binding assurance of certain properties or of suitability for a specific purpose. All Terms of Sale of Technical Lubricants International B.V. are applied here. **Updated 06/2021**